

## **ELECTRIC HEAT SEALER**

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

5           The present invention relates to an electric heat sealing apparatus and, more particularly, to a handy electric heat sealer, which can be held in hand and operated to seal the workpiece, or placed on a work table when sealing the workpiece. The electric heat sealer enables the sealing operation to be done at a time.

#### 10   2. Description of Related Art

          Electric heat sealing apparatus are commonly used in shops and stalls to seal polybags or the like, keeping packed foods or articles from contamination.

          However, regular electric heat sealing apparatus are commonly  
15   bulky and heavy, not practical for holding in hand when sealing the workpiece. When a conventional electric heat sealing apparatus is used, it must be placed on a worktable or the top of a desk or the like, and then press the movable arm to seal the workpiece. Further, when sealing the workpiece, for example, a polybag or the like with a conventional electric  
20   heat sealing apparatus, the hand holding the workpiece may hinder the sealing operation. Therefore, the user has to seal the workpiece from the middle area toward the two sides of the opening of the workpiece through several steps.

          Various prior art designs of electric heat sealing apparatus are

known. The inventor have also invented various designs of electric heat sealing apparatus, for example, the designs disclosed in Taiwan Patent Publication Nos. 370078; 370077; 356811; and etc.

## 5 SUMMARY OF THE INVENTION

The present invention has been accomplished under the circumstances in view. It is therefore the main object of the present invention to provide an electric heat sealer, which enables the user to hold the electric heat sealer in the left hand or right hand as desired and then to  
10 operate the electric heat sealer with the left or right hand, completing the sealing operation at one time. It is another object of the present invention to provide an electric heat sealer, which can be placed on a worktable and operated with one hand to seal the workpiece at one time. It is still another object of the present invention to provide an electric heat sealer, which is  
15 equipped with an operation case that assures safeness of the operation of the electric heat sealer, and causes a sense of beauty.

To achieve these and other objects of the present invention, the electric heat sealer is comprised of a first arm, an electric heating mechanism, and a second arm. The first arm has a coupling structure. The  
20 second arm has a coupling structure fastened pivotally with the coupling structure of the first arm for enabling the two arms to be turned relative to each other, and pressed together or moved apart. The first arm defines a receiving chamber, which accommodates the electric heating mechanism.

According to the present invention, the first arm and the second arm

each have a handhold portion. When the two arms pivotally fastened together, the user can hold the handhold portions of the two arms to move the electric heat sealer, and to press the heating member of the electric heating mechanism against the workpiece been put on one arm, causing the  
5 workpiece to be sealed.

Further, the first arm is a substantially T-shaped member having a left end portion and a right end portion aligned in a line. The combined length of the left end portion and right end portion of the first arm is within six to ten centimeters, or preferably at eight centimeters. The second arm is  
10 a substantially T-shaped member having a left end portion and a right end portion aligned in a line corresponding to the left end portion and right end portion of the first arm. The combined length of the left end portion and right end portion of the second arm is within six to ten centimeters, or preferably at eight centimeters. By means of the design of the left and right  
15 end portions at each arm, the user can hold the electric heat sealer with the left hand or the right hand as desired, and then operate the electric heat sealer with the left or right hand to seal the workpiece. Because the two arms are respectively shaped like a T-bar, the left or right end portions of the arms are extended to one lateral side of the workpiece, i.e. the heating  
20 member of the electric heating mechanism can be directly extended to one lateral side of the workpiece, enabling the user to seal the workpiece at one time.

Further, the first arm and second arm can be directly placed on a worktable when sealing the workpiece, i.e., the electric heat sealer can be

used as a palmtop electric heat sealer as well as a table electric heat sealer.

The invention further comprises an operation case. The operation case comprises a case body, a receiving chamber, and an opening. Through the opening, the handhold portions of the two arms can be inserted into the  
5 inside of the receiving chamber of the operation case. The operation case gives a protection to the user's hand during operation. The operation case can be made having any of a variety of ornamental design that causes a sense of beauty. After the electric heat sealer has been received in the operation case, the operation case can be conveniently placed on a  
10 worktable for pressing by hand to force the electric heat sealer to seal the workpiece.

The electric heat sealer can be used with battery. Alternatively, a power adapter may be installed in the electric heat sealer, enabling the electric heat sealer to obtain the necessary working voltage from an external  
15 power source. The position of the heating member of the electric heating mechanism is not limited to the first arm. Alternatively, the heating member of the electric heating mechanism can be installed in the second arm. If desired, two heating members may be used and respectively installed in the two arms.

20 Other objects, advantages, and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded view of an electric heat sealer according to the present invention.

FIG. 2 is a schematic drawing showing one application example of the electric heat sealer according to the present invention where the user  
5 operates the electric heat sealer with the right hand.

FIG. 3 is a schematic drawing showing another application example of the electric heat sealer according to the present invention where the user operates the electric heat sealer with the left hand.

FIG. 4 is a schematic drawing showing still another application  
10 example of the electric heat sealer according to the present invention where the electric heat sealer is operated by the user on a worktable.

FIG. 5 is an exploded view of the electric heat sealer and an operation case according to the present invention.

FIG. 6 is a schematic drawing showing an application example of  
15 the electric heat sealer with the operation case according to the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 is an exploded view of an electric heat sealer constructed  
20 according to the present invention. As illustrated, the electric heat sealer, referenced by 1, is comprised of a first arm 11 and a second arm 13. According to this embodiment, the first arm 11 and the second arm 13 have a substantially T-shaped profile. The first arm 11 has a left end portion 113 and a right end portion 114 aligned in a line. The second arm 13 has a left

end portion **133** and a right end portion **134** aligned in a line corresponding to the left end portion **113** and right end portion **114** of the first arm **11**. The combined length of the left end portion **113** and right end portion **114** of the first arm **11** is eight centimeters. The combined length of the left end  
5 portion **133** and right end portion **134** of the second arm **13** is also eight centimeters. This eight centimeters design is simply an example. In actual practice, the combined length can be set within six to ten centimeters. Further, the first arm **11** has a handhold portion **115**. The second arm **13** also has a handhold portion **132**. The handhold portion **115** of the first arm **1**  
10 defines a receiving chamber **111**, which accommodates an electric heating mechanism (not shown). Because the electric heating mechanism is similar to the electric heating mechanisms used in conventional electric heat sealers, no further detailed description in this regard is necessary.

As shown in FIG. 1, the first arm **11** has a coupling structure **112**  
15 disposed at one end remote from the left end portion **113** and the right end portion **114**. The second arm **13** has a coupling structure **131** disposed at one end remote from the left end portion **133** and the right end portion **134**. The coupling structures **112** and **131** are fastened pivotally together such that the first arm **11** and the second arm **13** can be turned relative to each  
20 other and pressed against each other, or moved apart. According to this embodiment, the coupling structures **112** and **131** are respectively comprised of recessed holes and protruding stub rods. Alternatively a pivot pin can be used to pivotally secure the first arm **11** and the second arm **13** together.

Referring to FIG. 2, after the first arm **11** and the second arm **13** have been pivotally coupled together, the user can hold the handhold portion **115** of the first arm **11** and the handhold portion **132** of the second arm **13** with the right hand **91** to move the electric heat sealer **1**, and then  
5 force the first arm **11** and the second arm **13** toward each other, causing the heating member **121** of the electric heat mechanism in the first arm **11** to press and heat the workpiece **92** against the second arm **13**. Therefore, the workpiece **92** is sealed. The workpiece **92** indicated in this and the following other embodiments of the present invention are a polybag.

10 FIG. 3 is a schematic drawing showing application example of the electric heat sealer **1** according to the present invention. As illustrated, the user holds the electric heat sealer **1** with the right hand **93** to seal the workpiece **94**. As illustrated in FIGS. 2 and 3, the design of the left end portions **113** and **133** and right end portions **114** and **134** of the first and  
15 second arms **11** and **13** enables the user to hold the electric heat sealer **1** directly with the right hand or left hand and to further seal the workpiece. Further, the design of the left end portions **113** and **133** and right end portions **114** and **134** of the first and second arms **11** and **13** enables the left end portions **113** and **133** or right end portions **114** and **134** to be extended  
20 to one lateral side of the workpiece **92** or **94** during sealing operation, so that the user can complete the sealing operation at one time.

FIG. 4 is a schematic drawing showing still another application example of the electric heat sealer **1**. As illustrated, the electric heat sealer **1** is directly put on a worktable **95**, working as a desktop electric heat sealer **1**.

Referring to FIGS. 5 and 6, the electric heat sealer 1 can be used with an operation case 2. When assembled, the electric heat sealer 1 can be put into the inside of the operation case 2. The operation case 2 comprises a case body 24, a receiving chamber 23, and an opening 25. The handhold portion 115 of the first arm 11 and the handhold portion 132 of the second arm 13 can be freely inserted through the opening 25 into the inside of the receiving chamber 23. Further, the case 2 has a top face 21 and an operation portion 22 at the top face 21 corresponding to the second arm 13. The operation portion 22 is supported on a spring member (not shown) in the operation case 2. The spring member can be a plastic spring plate, metal spring leaf, or compression spring. As shown in FIG. 6, after the electric heat sealer 1 had been received inside the operation case 2, the operation case 2 is put on a worktable 96 or the top of a table or the like, and the user can then press the operation portion 22 of the operation case 2 with the finger 98 to force the second arm 13 downwards against the workpiece 97 at the first arm 11 and to further seal the workpiece 97. During sealing operation, the user can pull the workpiece 97 leftwards or rightwards to adjust the position of the workpiece 97 in the electric heat sealer 1. Further, the operation case 2 has two notches 26 at two sides of the opening 25 corresponding to the heating member 121 of the electric heat sealer 1 for guiding movement of the workpiece 97 during heat sealing operation. Therefore, by means of the operation case 2, the electric heat sealer 1 can be put on the worktable 96 and operated to seal the workpiece 97. Further, the operation case 2 protects the user's hand during heat sealing operation. The



operation case 2 can be made having any of a variety of decorative design that causes a sense of beauty.

A prototype of electric heat sealer has been constructed with the features of FIGS. 1~6. The electric heat sealer functions smoothly to  
5 provide all of the features discussed earlier.

Although particular embodiments of the present invention have been described in detail for purposes of illustration, various modifications and enhancements may be made without departing from the scope of the invention. Accordingly, the invention is not to be limited except as by the  
10 appended claims.